

Supplier:	SolaLighting Limited, Sola House, 17 High Street, Olney, Bucks, MK46 4EB Tel: 01234 241466, Fax: 01234 241766 E-mail: info@solalighting.co.uk Web: www.solalighting.co.uk	
Product:	Solatube 21-C (530mm diameter, into ceiling)	Solatube 21-O (530 mm diameter, no ceiling, warehouse kit)
Solatube Base Kit:	<ul style="list-style-type: none"> • UV-stabilized polycarbonate roof dome with LightTracker™ dome reflector, covered by 10-year warranty against loss of light transmission, excessive yellowing and loss of impact strength • Solatube roof flashing for specified roof type * • 99.7% reflective Spectralight® Infinity top tube assembly incorporating pre-assembled dome ring with condensation filter • 99.7% reflective Spectralight® Infinity bottom tube incorporating adjustable 0-30° angle section 530mm round to 600 x 600mm transition box at ceiling level to fit suspended grid or drywall ceiling 600 x 600mm square clip-in OptiView® * or prismatic * ceiling diffuser • Plus all seals, sealants, fixings and installation instructions 	<ul style="list-style-type: none"> • UV-stabilized polycarbonate roof dome with LightTracker™ dome reflector, covered by 10-year warranty against loss of light transmission, excessive yellowing and loss of impact strength • Solatube roof flashing for specified roof type * • 99.7% reflective Spectralight® Infinity top tube assembly incorporating pre-assembled dome ring with condensation filter • 99.7% reflective Spectralight® Infinity 610mm long extension tube • Curved prismatic diffuser • Plus all seals, sealants, fixings and installation instructions
Extension tube sections:	99.7% Spectralight® Infinity rigid tube extensions to cover roof to ceiling distance	
Additional angle adaptors:	Additional 0-30° adjustable elbows are available if required.	
Performance criteria:	Standard reference BRE test report No 212921: transmittance efficiency (T) should not be less than 0.35 mean measurement in overcast sky conditions or 0.45 in simulated direct sunlight at a solar altitude of 58.1 degrees (solar azimuth 180 degrees from north) as certified by the Building Research Establishment for a reference tube length of 2.7m.	

* specify as required



SolaLighting Limited, Sola House, 17 High Street, Olney, Buckinghamshire, MK46 4EB
Tel 01234 241466 Fax 01234 241766
Email: solatube@solalighting.co.uk Website: www.solalighting.co.uk